



*Premium Luxury*

# CARPET GALLERIA

+971 55 575 9046 | +971 56 753 1109

Hamriyah Free Zone, Sharjah, UAE.

sales@cgalleria.com

Printed 1150gm

# DATASHEET

GENERAL PERFORMANCE OF CHROMOJET PRINTED CARPET			
Performance			
Color Fastness	EN 1307 ISO105-B02	Light 3	Dark 3.50
Light	EN 1307 ISO105-B02	Class 5	
Dry Rubbing	EN 1307 ISO105-X12	Class 5	
Wet Rubbing	EN 1307	Class 5	
Flammability			
Hot Metal Nut Test	BS 4790	Pass	
Methenamine Pill Test	ASTM D2859 / BS 6307	Pass	
Static Electricity	Anti Static GB/T18044-2000II		
Radiant Panel Test	EN 13501 - 1	B <sub>fl</sub> - s1	
Moth Proofing	EN 1815	Permethrin applied	
Performance Features			
Tolerances	All Specifications subject to normal manufacturing tolerances. Our Mills apply strict quality control at all stages of production; however as carpet manufacturing is a complex series of operation, slight variations in the weights & measurements quoted must be expected. Specifications are subject to change without notice but this will not have a detrimental effect on the performance of the product.		
Color Match	Although every effort is made to ensure color matching width to width, there may be variation dye batch to dye batch due to the inherent variability of the natural wool used in the blend.		
Shading/Pile Reversal	Cut-pile carpets, may show shading/pile reversal. This tendency is inherent in all cut pile fabrics and is not deter mental to the wear of the carpet. It cannot be considered a manufacturing defect. It should be noted and taken into consideration when selecting colors that darker shades camouflage soiling more than lighter shades. It applies particularly to contract installations.		



*Premium Luxury*

# CARPET GALLERIA

+971 55 575 9046 | +971 56 753 1109

Hamriyah Free Zone, Sharjah, UAE.

sales@cgallerya.com

Printed 1150gm

# DATASHEET

## TECHNICAL SPECIFICATIONS OF CHROMOJET PRINTED 1150GM

### Specification

<b>Manufacturing Process</b>	Chromojet Printed Machine Tufted Carpet
<b>Pile Composition</b>	100% Nylon PA
<b>Yarn Count</b>	3000 DTEX/62F/200Z
<b>Stitch Rate</b>	46S/10cm
<b>Pile Height</b>	+/- 7 mm
<b>Total Carpet Thickness</b>	+/- 9 mm
<b>Pile Weight</b>	+/- 1,150 gm/sqm
<b>Total Carpet Weight</b>	+/- 2,300 gm/sqm
<b>Primary Backing</b>	Polypropylene PP
<b>Secondary Backing</b>	Polyester
<b>Latex</b>	SBR Fray Resistant Latex Compound
<b>Latex Weight</b>	+/- 360gm/sqm