



Premium Luxury

CARPET GALLERIA

+971 55 575 9046 | +971 56 753 1109

Hamriyah Free Zone, Sharjah, UAE.

sales@cgalleria.com

Axminster 10 Rows

DATASHEET

GENERAL PERFORMANCE OF AXMINSTER CARPET			
Performance			
Color Fastness	EN 1307	Light 3	Dark 3.50
Light	EN 1307	≥ 4	
Dry Rubbing	EN 1307	≥ 3.50	
Wet Rubbing	EN 1307	≥ 3	
Flammability			
Hot Metal Nut Test	BS 4790	Pass	
Methenamine Pill Test	ASTM D2859 / BS 6307	Pass	
Static Electricity	Anti Static GB/T18044-2000II		
Radiant Panel Test	EN 13501 - 1	B _{fl} - s1	
Moth Proofing	EN 1815	Permethrin applied	
Performance Features			
Tolerances	All Specifications subject to normal manufacturing tolerances. Our Mills apply strict quality control at all stages of production; however as carpet manufacturing is a complex series of operation, slight variations in the weights & measurements quoted must be expected. Specifications are subject to change without notice but this will not have a detrimental effect on the performance of the product.		
Color Match	Although every effort is made to ensure color matching width to width, there may be variation dye batch to dye batch due to the inherent variability of the natural wool used in the blend.		
Shading/Pile Reversal	Cut-pile carpets, may show shading/pile reversal. This tendency is inherent in all cut pile fabrics and is not deter mental to the wear of the carpet. It cannot be considered a manufacturing defect. It should be noted and taken into consideration when selecting colors that darker shades camouflage soiling more than lighter shades. It applies particularly to contract installations.		



Premium Luxury

CARPET GALLERIA

+971 55 575 9046 | +971 56 753 1109

Hamriyah Free Zone, Sharjah, UAE.

sales@cgalleria.com

Axminster 10 Rows

DATASHEET

TECHNICAL SPECIFICATIONS OF AXMINSTER 7 x 10			
Specification			
Construction		Contract Woven Axminster	
Backing Materials	Weft	Jute/P.P. (or alternative Material or A mixture as available)	
	Warp	P.P./ Polyester /Poly Cotton	
Backing Coating		Non-fray latex	
		Metric	Imperial
Pile Composition		80% Wool	
		20% Nylon ±3%	
Pitch		27.56 per DM	7 per inch
Rows		35.43 per DM	10 per inch
Pile Height		7.6 mm (± 1.00 mm)	0.29 inch
Total Pile Weight		1,652 g/m ² (+15%/-10%)	48.00 oz/yd ² (+15%/-10%)
Total Carpet Weight		2,685 g/m ² (+/-15%)	79.20 oz/yd ² (+/-15%)
		Subject to variation depending on backing materials Used.	
Yarn Count	2ply	R660/2 Tex (±5%)	2/47s (±5%)
Loom sizes		3.66 or 4 meter	13.2
Suitability		Medium Contract	
Installation method		Glue-down or Stretching	